
FlowLite

Specification Sheet

FlowColor COB RGB+Tunable White IP68 LED Tape Light



FlowColor COB RGB+Tunable White IP68 is a wet-rated, full-color plus tunable-white COB LED tape light. IP68, 365 lumens per foot at 5.5 W/ft on a 14mm, 6-conductor board, 90 CRI, 26.25 ft reel, field cuttable every 1.61".

FEATURES & APPLICATIONS

- IP68, wet location rated
- RGB color plus tunable white
- 6-wire: V+, R, G, B, Warm White, Cool White
- 90 CRI (Color Rendering Index)
- 120° beam angle
- Field cuttable at every 1.61 inch
- Starters, couplings, clips and end caps included
- UL Listed, 3-year warranty

Performance

Color Temp	RGB + Tunable White
Watts/FT	5.5
Lumens/FT	365
Efficacy (Lm/W)	66
CRI	90

TECHNICAL INFORMATION

- **Power Consumption Per Foot:** 5.5 Watts (18 W/m)
- **Input Voltage:** 24V DC
- **Light Source:** COB, RGB + tunable white
- **CRI (Color Rendering Index):** 90
- **Output:** 365 lm/ft (1200 lm/m)
- **Wiring:** 6 wires (V+, R, G, B, WW, CW)
- **Width:** 0.55 inches (14mm)
- **Beam Angle:** 120°
- **Field Cuttable:** Every 1.61 inch
- **Max Run Length:** 32 ft.
- **Dimmable:** Yes, via RGB+Tunable White controller
- **Height:** 5.1mm
- **Mounting:** 3M 9495 300MP adhesive
- **Spool Lengths:** 26.25 ft. (8 m)
- **Environment:** Wet location (IP68)
- **In the box:** 2 hard-wire starters, 2 couplings with cord, 2 straight couplings
- **Listing:** UL Listed
- **Warranty:** 3 Year

ORDERING GUIDE

MODEL	COLOR	IP RATING	LENGTH
FL-CCOB-24-			
	RGBTW RGB+TW	**68** IP68, wet location	**26.25FT** (BLANK)

REQUIRED ACCESSORIES

Requires a controller and an RF remote to operate:



FL-CTL-RGBW
RGB+Tunable White Controller




FL-RMT-RGBW
RGB+Tunable White RF Remote

Pictures and specifications: see page 3.

DIMMABLE · IP20 · 24V · 90 CRI · 120° · 3 Yrs Warranty

DIAGRAM & DIMENSIONS



VOLTAGE DROP GUIDANCE CHART

24V Voltage Drop & Wire Length Distance Chart (3% Drop or 23.28V)

WIRE GAUGE	10 W .42 A	20 W .83 A	30 W 1.3 A	40 W 1.7 A	50 W 2.1 A	60 W 2.5 A	70 W 2.9 A	80 W 3.3 A	90 W 3.75 A	100 W 4.2 A
20 AWG	85 ft.	43 ft.	27 ft.	21 ft.	17 ft.	14 ft.	12 ft.	11 ft.	9 ft.	8 ft.
18 AWG	134 ft.	68 ft.	45 ft.	33 ft.	27 ft.	22 ft.	19 ft.	17 ft.	15 ft.	14 ft.
16 AWG	215 ft.	109 ft.	72 ft.	54 ft.	43 ft.	36 ft.	31 ft.	27 ft.	24 ft.	22 ft.
14 AWG	345 ft.	174 ft.	115 ft.	86 ft.	69 ft.	57 ft.	49 ft.	43 ft.	39 ft.	36 ft.
12 AWG	539 ft.	272 ft.	181 ft.	135 ft.	108 ft.	90 ft.	77 ft.	68 ft.	61 ft.	56 ft.
10 AWG	784 ft.	397 ft.	263 ft.	197 ft.	158 ft.	131 ft.	112 ft.	98 ft.	97 ft.	82 ft.

Note: These tables provide general guidelines for determining Wire Gauge based on total load and distance from LED driver to beginning of luminaire.

SAFETY, WARNINGS, AND DISCLOSURES

Install in accordance with national and local electrical code regulations.

This product to be powered with ELECTRONIC DRIVER ONLY

This product is intended to be installed and serviced by a qualified, licensed electrician.

Only use copper wiring. Use wires rated for at least 176°F 80°C and certified for use with external connection of electrical equipment.

Each maximum run requires a dedicated power feed from the driver. Do not extend beyond the recommended maximum run length.

Do not install product in an environment outside the listed ambient temperature. Exceeding the maximum ambient temperature may damage LED chips, reduce the total lamp life, lumen output, and/or adversely impact color consistency.


Tape light must be handled with care. Excessive handling, bending, and pressure may damage the product, voiding the warranty.

We reserve the right to modify and improve the design of our fixtures without prior notice. We cannot guarantee to match existing installed fixtures for subsequent orders or replacements in regards to product appearance, CCT, or lumen output.

REQUIRED ACCESSORIES

This RGB+Tunable White tape needs both items below to operate. The controller drives its color and white channels; the RF remote pairs with the controller. See the wiring diagram on page 2.





Product photo and dimensions

FL-CTL-RGBW

RGB+Tunable White Controller

Inline RF controller. Sets RGB color, tunes white and dims; installs between the 24V DC driver and the tape.

Input	12–24V DC (from a constant-voltage driver)
Control	RF wireless remote
Function	RGB color, tunable white, dimming
Dimensions	4.48” × 1.49” × 0.78” (4.89” long with mounting tabs)
Operating temperature	-4°F to 131°F

FL-RMT-RGBW

RGB+Tunable White RF Remote

Handheld RF remote for the FL-CTL-RGBW controller: color, white tuning and dimming.

Control	RF wireless
Pairs with	FL-CTL-RGBW controller
Dimensions	4.21” × 2.30” × 0.35”