FlowLite

Specification Sheet
Corner Wall Wash 0.55 Channel

Corner Wall Wash 0.55 FL-WW55C

A corner-mounted wall wash that grazes walls from the ceiling line with hidden tape.

PRODUCT INFORMATION

Model	FL-WW55C
Category	Wall Wash / Indirect
Aperture (inner width)	0.55" (14.0 mm)
Overall width	1.46" (37.1 mm)
Length	96" (8 ft) per piece
Max tape width	12 mm
Max tape power	15 W/m (4.6 W/ft)
Material	Extruded aluminum
Finish	Anodized silver
Diffuser	Opal (frosted) polycarbonate
End caps	PVC
Field cuttable	Yes
Location	Dry location



FEATURES

- Wall-wash optic
- Corner mount
- Up to 12 mm tape
- 8 ft kit
- Field-cuttable aluminum body and diffuser in 96" lengths


ORDERING GUIDE

MODEL NUMBER **FL-WW55C-SV-OP-8**

MODEL		FINISH		DIFFUSER		LENGTH
FL-WW55C	–	SV Anodized silver	–	OP Opal polycarbonate	–	8 96" (8 ft)

Each kit includes: 1 x 96" profile, 1 x 96" opal diffuser, 2 x end caps

DIMENSIONS



KEY DIMENSIONS

Aperture	0.55" (14.0 mm)
Overall width	1.46" (37.1 mm)
Length	96" (2438 mm)
Max tape width	12 mm

Dimensions in inches. Drawing not to scale. Allow for the tape lead and end caps when planning cut lengths.

ACCESSORIES

FL-WW55C-EC
End cap
Included with kit; spare

FL-WW55C-DF
Opal diffuser, 96" (spare)
Included with kit; spare